



KM STEEL



Handle for practical use



Single central bar for vertical lifting with crane or winches



Professional control panel. Electronic temperature regulation system with low oscillation of the set value.

TSR



Triplex pumps with ceramic pistons and brass pump head

FOR MORE INFORMATION



Professional pressure-release unloader valve



Detergent regulator with connector on the front



Front and rear protective bumper also useful for improving maneuverability and safety in manual lifting operations



BOX DIMENSION (cm)	100 x 73 x 105
QUANTITY FOR PALLET	1
PALLET DIMENSION (cm)	100 x 73 x 105
N. MACHINES CONTAINER 20'	34
N. MACHINES CONTAINER 40' (40' HQ)	68

Motor-pump coupling with a flexible joint (7,5 / 10 HP models only)



GENERAL FEATURES

- 25 lt fuel tank with level float
- High-pressure detergent suction with proportional detergent regulation
- 4 big solid wheels (Ø 260 mm) + brake
- Water tank with cartridge filter and floater
- Anti-scale device with pump and tank (2,5 l - ON REQUEST)
- Professional 4-pole motor (1400 giri/min) with flexible joint (7,5 / 10 HP models only)
- Professional pressure unloader valve
- 15 seconds Delayed Total Stop
- General stop when the machine is not used for a long time (30 minutes)
- EASY START on 1-230 model
- Boiler with stainless steel casing (7,5 / 10 HP models only)
- Electronic temperature regulation system with low oscillation of the set value
- PED 2014/68/CE cat. II certification
- Flow-switch controlled burner
- Flame control
- Safety valve
- Boiler thermal protection
- Pressure gauge with S.S. frame

TECHNICAL FEATURES

CODE	MODELS	PUMP																				
			Ph	V	Hz	bar	MPa	bar	MPa	l/h	HP	kW	kW	°C	kg/h	kg	(L x W x H) cm					
9076 0001	KM Steel Extra 11/120	ZW	1	230	50	120	12	30÷110	3÷11	340÷660	3	2,2	2,9	85÷140	3,5	145	90 x 65 x 87					
9076 0002	KM Steel Extra 13/190	ZW	3	400	50	190	19	30÷180	3÷18	320÷780	5,5	4	5,0	85÷140	4,6	150	90 x 65 x 87					
9076 0003	KM Steel Extra 15/170	ZW	3	400	50	170	17	30÷160	3÷16	390÷900	5,5	4	5,0	85÷140	5,5	150	90 x 65 x 87					
9076 0004	KM Steel Extra 16/200	FW2	3	400	50	200	20	30÷190	3÷19	350÷960	7,5	5,5	6,0	85÷140	5,7	160	90 x 65 x 87					
9076 0005	KM Steel Extra 21/160	FW2	3	400	50	160	16	30÷150	3÷15	450÷1260	7,5	5,5	6,5	85÷140	6,5	160	90 x 65 x 87					
9076 0006	KM Steel Extra 21/200	FW2	3	400	50	200	20	30÷190	3÷19	450÷1260	10	7,5	8,5	85÷140	7,0	170	90 x 65 x 87					

STANDARD EQUIPMENT



GH 401 gun with swivel

TECHNICAL FEATURES					COMPATIBLE MODELS					
l/min	IN	OUT	bar	CODE	9076 0001	9076 0002	9076 0003	9076 0004	9076 0005	9076 0006
40	G 3/8" M	M22x1,5 F	400	2410 0277						



Bent lance with detergent head, without nozzle

TECHNICAL FEATURES				COMPATIBLE MODELS					
IN	OUT	mm	CODE	9076 0001	9076 0002	9076 0003	9076 0004	9076 0005	9076 0006
M22x1,5 M	1/4" F NPT	760	3301 0974						



Fan shape nozzle

TECHNICAL FEATURES				COMPATIBLE MODELS					
IN	Ø		CODE	9076 0001	9076 0002	9076 0003	9076 0004	9076 0005	9076 0006
1/4" NPT M	040	25	3400 0702						
1/4" NPT M	045	25	3400 0703						
1/4" NPT M	050	25	3400 0705						
1/4" NPT M	070	25	3400 0711						
1/4" NPT M	065	25	3400 0710						



Rubber delivery hose kit

TECHNICAL FEATURES				COMPATIBLE MODELS					
IN	OUT	m	CODE	9076 0001	9076 0002	9076 0003	9076 0004	9076 0005	9076 0006
M22x1,5 F - Ø14	G 3/8" F	10 - R1 1/4"	3208 1050						
M22x1,5 F - Ø14	G 3/8" F	10 - R1 5/16"	3301 0987						
M22x1,5 F - Ø14	G 3/8" F	10 - R2 5/16"	3301 0776						
M22x1,5 F - Ø14	G 3/8" F	10 - R2 3/8"	3301 0944						



Flame control kit

				COMPATIBLE MODELS					
CODE				9076 0001	9076 0002	9076 0003	9076 0004	9076 0005	9076 0006
5018 0081									